

Modulo

Compact, two-colour, electro-pneumatic pad printing machine:

- 2 closed ink cups (Ø 90, Ø 130 or Ø 160 or mixed)
- Pad cleaning
- PLC controlled
- Operated by touch screen panel
- Executed with 1 jig on a XY table on one position
- Executed with rotary table for two or four positions for automation with re-treatment, end-drying or ejection of the objects.

Direct connection of the table and/or jig to the machine without the need for additional wiring. When the option is connected and the machine is restarted, the new additional features are automatically enabled by the software.

The jig and rotary table are designed in this way that they allow the customer to control different types of jigs flexibly, without the need for reprogramming or rewiring the machine.

This option module can control 2 cylinders (with end detections), one vacuum unit or product clamp and one part detection. The functionality of these can be fully programmed by the customer by using the touch screen operation panel.



Model	Max print	No of colors	Speed
Modulo 90x2	75 mm Ø	1 or 2	Max. 1000 cycles/h
Modulo 130x2	115 mm Ø	1 or 2	Max. 1000 cycles/h
Modulo 160x2	140 mm Ø	1 or 2	Max. 1000 cycles/h

Website: www.amtecinc.com

Email : sales@amtecinc.com

APPLIED MANUFACTURING TECHNOLOGIES, INC.

3565 E. Enterprise Drive, Anaheim, CA 92807

Tel: 714-630-9530 Fax: 714-630-9531 Toll Free: 888-634-1143