



Applied Manufacturing Technologies, Inc.

Tel: (714) 630-9530
 Website: www.amtecinc.com
 E-Mail: sales@amtecinc.com

Sealed Ink Cup - Specifications

Model	60 E	90 E	130 E	90 Q	130 Q
Number of Colors	1	1	1	1	1
Single Cycle	Yes	Yes	Yes	Yes	Yes
Ink cup diameter	60 mm	90 mm	130 mm	90 mm	130 mm
Print size (Ø) max.	55 mm	85 mm	120 mm	80 x (160 / 320 / 520)	120 x (340 / 540)
Speed / Cycles per hour	Up to 1500	Up to 1400	Up to 1250	Up to 600	Up to 600
Cliche size, max	70 x 140 mm	100 x 215 mm	150 x 300 mm	100 x (440 / 600 / 800)	150 x (730 / 930)
Pad stroke onto cliché	80 mm	100 mm	35 – 80 mm	10 - 130	10 - 130
Printing pressure N (lbs)	450 (101)	750 (169)	1800 (405)	750 (169)	1800 (405)
Continuous Run	Yes	Yes	Yes	Yes	Yes
Pad stroke	20- 80 mm	35 – 100 mm	25 -120 mm	35 – 100 mm	25 -120 mm
Drive	Electro-pneumatic	Electro-pneumatic	Electro-pneumatic	Electro-pneumatic	Electro-pneumatic
Control	PLC	PLC	PLC	PLC	PLC
Air consumption per cycle	1.3 NL	2.7 NL	6 NL	2.7 NL	6 NL
Auto-Pad Cleaning	Optional	Optional	Optional	Optional	Optional
Multiple Print (selectable)	1 - 3	1 - 4	1 - 4	1 - 4	1 - 4
Dimensions: (W x D x H) mm (inches)	342 x 665 x 480 (14 x 26 x19)	372 x 810 x 640 (15 x 32 x 25)	436 x 1042 x 794 (17 x 41 x 31)	1114 x 1166 x 1600 (44 x 46 x 63)	1440 x 1560 x 1140 (57 x 61 x 45)
Weight: Kg (lbs)	42 (93)	76 (168)	134 (295)	265 (584)	1000 (2205)