



Applied Manufacturing Technologies, Inc.

Tel: (714) 630-9530

Website: www.amtecinc.com

E-Mail: sales@amtecinc.com

Hermetic - Specifications

Model	Hermetic 612 Universal	Entrance 90	Hermetic 912 Universal	Hermetic 13-12 Universal	Hermetic 150 Universal
Number of Colors	1	1	1	1	1
Single Cycle	Yes	Yes	Yes	Yes	Yes
Ink cup diameter	60 mm	90 mm	90 mm	130 mm	150 mm
Print size (Ø) max.	55 mm	85 mm	85 mm	120 mm	140 mm
Speed / Cycles per hour	1,300-4,100	600-1,700	1,100-3,600	1,000-2,700	750-2,100
Cliché size	70 x 140 mm	100 x 215 mm	100 x 215 mm	150 x 300 mm	160 x 350 mm
Pad stroke mm	110	110 – 150	110 – 150	120 – 160	160 – 190
Printing pressure N (lbs)	300 (67)	700 (160)	1,100 (247)	1,800 (405)	2500 (562)
Continuous Run	Yes	Yes	Yes	Yes	Yes
Control Voltage	24 V/DC	24 V/DC	24 V/DC	24 V/DC	24 V/DC
Drive	Electro-mechanical	Electro-mechanical	Electro-mechanical	Electro-mechanical	Electro-mechanical
Control	PLC	PLC	PLC	PLC	PLC
Multiple Print (programmable)	1 - 4	1 - 2	1 - 4	1 - 4	1 - 4
Auto-Pad Cleaning	Optional	No	Optional	Optional	Optional
Dimensions: (W x D x H) mm (inches)	323 x 811 x 750 (13 x 32 x 30)	550 x 590 x 1620 (22 x 23 x 64)	360 x 1000 x 870 (14 x 39 x 34)	393 x 1175 x 1076 (15 x 46 x 42)	490 x 1073 x 1770 (19 x 42 x 70)
Weight: Kg (lbs)	70 (154)	155 (342)	156 (344)	266 (586)	510 (1124)