



Applied Manufacturing Technologies, Inc.

Tel: (714) 630-9530

Website: www.amtecinc.com

E-Mail: sales@amtecinc.com

Rapid 2000 - Specifications

Model	Rapid 2000 / 60-3	Rapid 2000 / 90	Rapid 2000 / 130
Number of Colors	1	1	1
Single Cycle	Yes	Yes	Yes
Ink cup diameter	60	90	130 (option : 140)
Print size (Ø) max.	55	85	125 (option : 130)
Speed / Cycles per hour	1500 - 6000	1300 - 5400	1700 - 4500
Cliché size	70 x 140	100 x 215	150 x 300
Pad stroke mm	84	123	160
Printing pressure N (lbs)	500 (112)	1500 (337)	2000 (450)
Continuous Run	Yes	Yes	Yes
Control Voltage	24 V/DC	24 V/DC	24 V/DC
Drive	Electro-mechanical	Electro-mechanical	Electro-mechanical
Control	PLC	PLC	PLC
Multiple Print (1-4 programmable)	Yes	Yes	Yes
Auto-Pad Cleaning	Optional	Optional	Optional
Dimensions: (W x D x H) mm (inches)	550x261x595	706x327x675	940x394x825
Weight: Kg (lbs)	60 (132)	90 (198)	205 (452)